

```

[tanish@localhost ddd-3.3.9]$ make
Making all in themes
make[1]: Entering directory `/home/tanish/ddd-3.3.9/themes'
make[1]: Nothing to be done for `all'.
make[1]: Leaving directory `/home/tanish/ddd-3.3.9/themes'
Making all in vsllib
make[1]: Entering directory `/home/tanish/ddd-3.3.9/vsllib'
make[1]: Nothing to be done for `all'.
make[1]: Leaving directory `/home/tanish/ddd-3.3.9/vsllib'
Making all in ddd
make[1]: Entering directory `/home/tanish/ddd-3.3.9/ddd'
make all-am
make[2]: Entering directory `/home/tanish/ddd-3.3.9/ddd'
cat ./host.h.in | \
/bin/sed "s%@HOST_CANONICAL@%i686-pc-linux-gnu%" | \
/bin/sed "s%@TARGET_CANONICAL@%i686-pc-linux-gnu%" | \
  cat > host.h~ && mv host.h~ host.h
cat ./root.h.in | \
/bin/sed "s%@ROOT@%/usr/local/share/ddd-3.3.9%" | \
/bin/sed "s%@ALT_ROOT@%/usr/local/share/ddd%" | \
  cat > root.h~ && mv root.h~ root.h
if g++ -DHAVE_CONFIG_H -I. -I. -I. -I./.. -isystem /usr/OpenMotif-2.1.31/include
-isystem /usr/X11R6/include -O2 -g -Wall -W -Wwrite-strings -trigraphs -MT ddd.o
-MD -MP -MF ".deps/ddd.Tpo" -c -o ddd.o ddd.C; \
then mv -f ".deps/ddd.Tpo" ".deps/ddd.Po"; else rm -f ".deps/ddd.Tpo"; exit 1; fi
if g++ -DHAVE_CONFIG_H -I. -I. -I. -I./.. -isystem /usr/OpenMotif-2.1.31/include
-isystem /usr/X11R6/include -O2 -g -Wall -W -Wwrite-strings -trigraphs -MT exit.o
-MD -MP -MF ".deps/exit.Tpo" -c -o exit.o exit.C; \
then mv -f ".deps/exit.Tpo" ".deps/exit.Po"; else rm -f ".deps/exit.Tpo"; exit 1; fi
if g++ -DHAVE_CONFIG_H -I. -I. -I. -I./.. -isystem /usr/OpenMotif-2.1.31/include
-isystem /usr/X11R6/include -O2 -g -Wall -W -Wwrite-strings -trigraphs -MT
resolveP.o -MD -MP -MF ".deps/resolveP.Tpo" -c -o resolveP.o resolveP.C; \
then mv -f ".deps/resolveP.Tpo" ".deps/resolveP.Po"; else rm -f ".deps/resolveP.Tpo";
exit 1; fi
cat Ddd | cat | \
/bin/sed -n -f ./ad2c.sed > Ddd.ad.h~ && mv Ddd.ad.h~ Ddd.ad.h
if g++ -DHAVE_CONFIG_H -I. -I. -I. -I./.. -isystem /usr/OpenMotif-2.1.31/include
-isystem /usr/X11R6/include -O2 -g -Wall -W -Wwrite-strings -trigraphs -MT
resources.o -MD -MP -MF ".deps/resources.Tpo" -c -o resources.o resources.C; \
then mv -f ".deps/resources.Tpo" ".deps/resources.Po"; else rm -f
".deps/resources.Tpo"; exit 1; fi
if g++ -DHAVE_CONFIG_H -I. -I. -I. -I./.. -isystem /usr/OpenMotif-2.1.31/include

```

```
-isystem /usr/X11R6/include -O2 -g -Wall -W -Wwrite-strings -trigraphs -MT
show.o -MD -MP -MF ".deps/show.Tpo" -c -o show.o show.C; \
then mv -f ".deps/show.Tpo" ".deps/show.Po"; else rm -f ".deps/show.Tpo"; exit 1; fi
/bin/sh ../libtool --mode=link g++ -O2 -g -Wall -W -Wwrite-strings -trigraphs -o
ddd ddd.o assert.o basename.o compare.o cook.o cwd.o glob.o hash.o home.o isid.o
rxclass.o sigName.o strclass.o tabs.o uniquify.o Logger.o MemCheck.o PrintGC.o
SignalB.o TypeInfo.o UniqueId.o Agent.o AgentM.o AsyncAgent.o ChunkQueue.o
DataLength.o HandlerL.o LiterateA.o ReadLineA.o TimeOut.o TTYAgent.o
charsets.o converters.o events.o findParent.o findWindow.o fileSBF.o frame.o
longName.o selection.o verify.o AutoRaise.o Delay.o DeleteWCB.o DestroyCB.o
ExitCB.o InitImage.o Swallower.o XErrorB.o freeXmST.o LabelH.o LessTiff.o
MakeMenu.o MString.o ComboBox.o SpinBox.o TextSetS.o printBox.o AlignBox.o
ArcBox.o BinBox.o Box.o BoxD.o BoxExtend.o BoxPoint.o BoxRegion.o BoxSize.o
ColorBox.o CompositeB.o DiagBox.o DummyBox.o FixBox.o FontFixBox.o
FontTable.o HatBox.o LineBox.o ListBox.o MarkBox.o MatchBox.o PrimitiveB.o
SlopeBox.o StringBox.o THatBox.o TagBox.o TrueBox.o ArgNode.o BuiltinCN.o
CallNode.o ConstNode.o DefCallN.o DummyNode.o LetNode.o NameNode.o
ListNode.o TestNode.o ThemeVSL.o TrueNode.o VSEFlags.o VSLArgList.o
VSLBuiltin.o VSLDef.o VSLDefList.o VSLerr.o VSLLib.o VSLNode.o VSLRead.o
ArcGraphE.o BoxEdgeA.o BoxGraphN.o EdgeA.o Graph.o GraphEdge.o
GraphEdit.o GraphGC.o GraphNode.o HintGraphN.o LineGraphE.o LineGESI.o
PannedGE.o PosGraphN.o RegionGN.o ScrolledGE.o layout.o annotation.o args.o
buttons.o cmdtty.o comm-manag.o complete.o ctrl.o data.o dbx-lookup.o decoration.o
deref.o disp-read.o editing.o environ.o examine.o exectty.o exit.o expired.o file.o
filetype.o fonts.o fortranize.o gdbinit.o history.o hostname.o index.o java.o logo.o
logplayer.o mainloop.o mydialogs.o options.o plotter.o post.o print.o question.o
regexps.o resolveP.o resources.o sashes.o select.o session.o settings.o shell.o
shorten.o show.o simpleMenu.o source.o status.o string-fun.o tempfile.o tictactoe.o
tips.o toolbar.o ungrab.o value-read.o vsldoc.o windows.o wm.o xconfig.o AliasGE.o
ArgField.o BreakPoint.o CodeCache.o Command.o DataDisp.o DispBox.o
DispBuffer.o DispGraph.o DispNode.o DispValue.o DispValueT.o GDBAgent.o
HelpCB.o HistoryD.o PlotAgent.o PlotArea.o PosBuffer.o ProgressM.o RefreshDI.o
SmartC.o SourceView.o ThemeM.o ThemeP.o Tool.o UndoBuffer.o UndoBE.o
WhatNextCB.o configinfo.o -L/usr/OpenMotif-2.1.31/lib -L/usr/X11R6/lib -lXm
-lXaw -lXmu -lXt -lXpm -lXp -lXext -lSM -lICE -lX11 -lncurses -lm -lm
g++ -O2 -g -Wall -W -Wwrite-strings -trigraphs -o ddd ddd.o assert.o basename.o
compare.o cook.o cwd.o glob.o hash.o home.o isid.o rxclass.o sigName.o strclass.o
tabs.o uniquify.o Logger.o MemCheck.o PrintGC.o SignalB.o TypeInfo.o UniqueId.o
Agent.o AgentM.o AsyncAgent.o ChunkQueue.o DataLength.o HandlerL.o
LiterateA.o ReadLineA.o TimeOut.o TTYAgent.o charsets.o converters.o events.o
findParent.o findWindow.o fileSBF.o frame.o longName.o selection.o verify.o
```

```

AutoRaise.o Delay.o DeleteWCB.o DestroyCB.o ExitCB.o InitImage.o Swallower.o
XErrorB.o freeXmST.o LabelH.o LessTifH.o MakeMenu.o MString.o ComboBox.o
SpinBox.o TextSetS.o printBox.o AlignBox.o ArcBox.o BinBox.o Box.o BoxD.o
BoxExtend.o BoxPoint.o BoxRegion.o BoxSize.o ColorBox.o CompositeB.o
DiagBox.o DummyBox.o FixBox.o FontFixBox.o FontTable.o HatBox.o LineBox.o
ListBox.o MarkBox.o MatchBox.o PrimitiveB.o SlopeBox.o StringBox.o THatBox.o
TagBox.o TrueBox.o ArgNode.o BuiltinCN.o CallNode.o ConstNode.o DefCallN.o
DummyNode.o LetNode.o NameNode.o ListNode.o TestNode.o ThemeVSL.o
TrueNode.o VSEFlags.o VSLArgList.o VSLBuiltin.o VSLDef.o VSLDefList.o
VSLerr.o VSLLib.o VSLNode.o VSLRead.o ArcGraphE.o BoxEdgeA.o
BoxGraphN.o EdgeA.o Graph.o GraphEdge.o GraphEdit.o GraphGC.o GraphNode.o
HintGraphN.o LineGraphE.o LineGESI.o PannedGE.o PosGraphN.o RegionGN.o
ScrolledGE.o layout.o annotation.o args.o buttons.o cmdtty.o comm-manag.o
complete.o ctrl.o data.o dbx-lookup.o decoration.o deref.o disp-read.o editing.o
environ.o examine.o exectty.o exit.o expired.o file.o filetype.o fonts.o fortranize.o
gdbinit.o history.o hostname.o index.o java.o logo.o logplayer.o mainloop.o
mydialogs.o options.o plotter.o post.o print.o question.o regexps.o resolveP.o
resources.o sashes.o select.o session.o settings.o shell.o shorten.o show.o
simpleMenu.o source.o status.o string-fun.o tempfile.o tictactoe.o tips.o toolbar.o
ungrab.o value-read.o vsldoc.o windows.o wm.o xconfig.o AliasGE.o ArgField.o
BreakPoint.o CodeCache.o Command.o DataDisp.o DispBox.o DispBuffer.o
DispGraph.o DispNode.o DispValue.o DispValueT.o GDBAgent.o HelpCB.o
HistoryD.o PlotAgent.o PlotArea.o PosBuffer.o ProgressM.o RefreshDI.o SmartC.o
SourceView.o ThemeM.o ThemeP.o Tool.o UndoBuffer.o UndoBE.o WhatNextCB.o
configinfo.o -L/usr/OpenMotif-2.1.31/lib -L/usr/X11R6/lib -lXm -lXaw -lXmu -lXt
-lXpm -lXp -lXext -lSM -lICE -lX11 -lncurses -lm
/bin/sed -f ./unumlaut.sed ddd.man | cat > ddd.1~ \
    && mv ddd.1~ ddd.1
make[2]: Leaving directory `/home/tanish/ddd-3.3.9/ddd'
make[1]: Leaving directory `/home/tanish/ddd-3.3.9/ddd'
make[1]: Entering directory `/home/tanish/ddd-3.3.9'
make[1]: Nothing to be done for `all-am'.
make[1]: Leaving directory `/home/tanish/ddd-3.3.9'
[tanish@localhost ddd-3.3.9]$

```